

パッキン 定価表(全面)

2023年6月1日版

R1

品番	NO.610					V6500					V6502					天然ゴム				V7010		品番
	ノンアス					ノンアス					ノンアス (高温用)									オールテフロン		
	1.5t		3t		組F用	1.5t		3t			1.5t		3t			3t				3t		
厚み	5K	10K	5K	10K		5K	10K	5K	10K	20K	5K	10K	5K	10K	20K	5K	10K	20K	上水	5K	10K	
15A	170	230	300	420	180	320	340	580	660	660	390	530	770	900	900	80	90	90		1,330	1,640	15A
20A	190	270	320	440	190	380	390	600	720	720	410	560	810	1,000	1,000	90	100	100		1,510	2,110	20A
25A	230	360	410	700	240	440	570	860	1,150	1,150	480	840	1,060	1,490	1,490	100	120	120		2,380	2,970	25A
32A	340	450	600	800	350	600	630	1,060	1,270	1,270	700	940	1,400	1,750	1,750	130	150	150		2,720	3,610	32A
40A	380	480	650	870	400	660	740	1,130	1,600	1,600	760	1,050	1,580	1,930	1,930	150	200	200		3,150	3,790	40A
50A	400	590	740	1,020	420	770	920	1,320	1,810	1,810	880	1,250	1,720	2,590	2,590	180	250	250	250	3,840	4,720	50A
65A	580	720	1,030	1,270	590	920	1,080	1,730	2,240	2,240	1,170	1,520	2,690	3,360	3,360	230	300	300	340	4,890	5,390	65A
80A	750	940	1,300	1,440	780	1,350	1,400	2,080	2,300	2,560	1,640	1,750	3,120	3,500	3,700	260	320	340	340	5,540	5,830	80A
100A	910	1,050	1,650	1,800	950	1,800	1,880	2,670	2,900	3,530	1,840	2,220	3,720	4,070	4,440	330	360	500	380	7,300	7,620	100A
125A	1,240	1,390	2,230	2,450	1,260	1,960	2,110	3,350	3,570	4,390	2,560	3,100	4,920	5,200	6,520	430	440	650	600	10,280	11,410	125A
150A	1,540	1,710	2,700	2,990	1,590	2,600	2,690	4,180	4,240	5,050	3,210	3,840	6,430	6,560	7,670	680	700	860	720	13,910	14,740	150A
200A	2,160	2,310	3,750	3,960		3,650	3,700	6,230	6,350	7,100	4,840	5,490	8,260	8,770	9,890	850	970		900	16,600	17,490	200A
250A	2,990	3,190	5,120	5,580		5,000	5,100	8,040	8,360	9,850	6,650	7,140	15,110	16,110	17,170	1,150	1,300			20,520	22,530	250A
300A	3,600	3,900	6,270	6,720		6,880	7,080	11,480	11,790	13,700	9,240	9,500	18,060	20,270	21,190	1,400	1,500			26,130	27,720	300A

	No.610	V6500	V6502	V7030	オールテフロン	天然ゴム	ポルテックス内外鉄
水	◎	◎	◎	◎	◎	◎	◎
温水	◎	◎	◎	◎	◎	△	◎
蒸気	×	×	○	×	×	×	◎

流体が油、酸、薬液等の場合は流体名をご確認の上お問合せ下さい

ご不明な点がございましたら弊社営業までお問い合わせください。

蒸気用パッキン選定 (10K以内)	耐温度	目安
V6502		120°C
T1120		180°C
V7020 充填剤入り		200°C
GF300		240°C
ポルテックス内外輪鉄		350°C

No.610,V6500,V7030につきましては
蒸気不可で100°C以内です。

