

# パッキン価格表(全面)

2015/3月

品番	No.610				V6500					V6502					天然ゴム				NBRネオプレン相当品			オールテフロン		No.610
	ノンアス				ノンアス					ノンアス(高温用)									CNRスーパー3t			3t		1.5t
厚み	1.5t		3t		1.5t		3t			1.5t		3t			3t				CNRスーパー3t			3t		1.5t
寸法 全周	5K	10K	5K	10K	5K	10K	5K	10K	20K	5K	10K	5K	10K	20K	5K	10K	20K	上水	5K	10K	上水	5K	10K	組F用
15A	120	170	215	290	190	215	320	360	360	320	440	640	740	740	64	64	64		70	90		1,080	1,320	120
20A	145	200	240	320	210	225	350	380	380	380	460	720	820	820	68	72	72		90	100		1,240	1,720	145
25A	170	265	290	500	280	335	480	560	560	420	690	840	1,250	1,250	72	84	84		140	220		1,920	2,400	170
30A	250	340	435	570	360	405	600	680	680	585	760	1,180	1,380	1,380	100	120	120		240	280		2,240	2,880	250
40A	300	360	480	610	380	480	640	800	800	650	855	1,290	1,600	1,600	120	160	160		270	330		2,560	3,120	300
50A	320	435	530	740	460	550	760	920	1,160	755	1,080	1,480	2,080	2,200	145	185	230	220	340	440	560	3,120	3,840	320
65A	435	540	735	920	580	695	980	1,160	1,440	1,060	1,260	2,105	2,560	2,800	185	220	280	300	400	510	720	3,960	4,400	436
75A	565	610	960	1,040	840	860	1,200	1,240	1,520	1,360	1,520	2,560	2,760	3,030	210	240	300	300	580	600	800	4,560	4,800	565
100A	690	800	1,180	1,300	1,060	1,120	1,520	1,600	2,000	1,400	2,020	3,040	3,560	3,880	265	290	440	320	620	660	1,120	6,000	6,040	690
125A	925	1,060	1,560	1,780	1,260	1,370	1,800	1,960	2,400	2,250	2,600	4,120	4,320	4,720	340	385	580	520	670	880	1,560	8,400	9,200	925
150A	1,160	1,280	1,940	2,160	1,645	1,680	2,350	2,400	3,000	2,920	3,240	5,200	5,400	5,900	475	560	760	640	1,010	1,340	1,960	11,200	12,000	1,160
200A	1,640	1,740	2,740	2,940	2,320	2,380	3,320	3,400	4,250	4,240	4,360	7,060	7,480	8,200	720	780	880	800	1,640	1,720	2,120	13,600	14,400	
250A	2,240	2,400	3,760	4,080	3,270	3,360	4,680	4,800	6,980	4,950	5,620	10,100	10,800	12,000	940	1,020	1,280	1,120	2,160	2,440	3,200	16,800	18,600	
300A	2,720	2,920	4,600	5,000	4,380	4,480	6,270	6,400	9,270	7,650	7,700	14,100	14,400	16,600	1,120	1,200	1,400	1,450	3,200	3,400	4,040	21,500	22,800	

	No.610ノンアスシート	V6500	V6502	V7030	オールテフロン	天然ゴム	CNRスーパー	ボルテックス内外鉄
水	◎	◎	◎	◎	◎	◎	◎	◎
温水	◎	◎	◎	◎	◎	△	○	◎
蒸気	×	×	○	×	×	×	×	◎
油	×	×	◎	△	○	×	◎	◎
高温油	×	×	△	×	×	×	×	◎
常温酸	×	×	×	○	◎	×	×	×

ボルテックス内外綷鉄	350°C
V7020 充填剤入りテフロンサント	200°C
V6502	150°C
バルカーGF300	240°C

No.610,V6500,V7030につきましてはスチーム不可で100°C以内です。

不明な点は弊社営業までお問い合わせ下さい。

